



(1) 1/2-13 UNC-3B X 1.12 DEEP

(4) 1/2-13 UNC-2B X .75 DEEP ON A ø7.250 B.C.

(2) ø1.13 CONDUIT HOLE (PLUGGED)

DASH NO.	"C"	"AD"
1050	20.76	4.25
1100	21.26	4.75
1150	21.76	5.25
1200	22.26	5.75
1250	22.76	6.25
1300	23.26	6.75
1350	23.76	7.25
1400	24.26	7.75

MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY TO BE .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT .009 T.I.R.
 ALIGN BASE TO C-FACE MOUNTING HOLES WITHIN ±1/16"

NO.		REVISION	BY & DATE	CHK	ANG	±1/2'	FINISH	STOCK	SIZE	DRAWING NO.	REV.
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT											
							TOLERANCES UNLESS SPECIFIED DEC. INCHES .X ±.1 .XX ±.03 .XXX ±.005 .XXXX ±.0005		ELECTRIC MOTORS GEARMOTORS AND DRIVES LEESON		DRAWN LST 5/6/05 CHK APPD SCALE 3=8 REF OL140668 FMF 140668 PREV
							TITLE OUTLINE - 215JP FRAME DRIP PROOF - RIGID "C"		CAD FILE 037623		B 037623