



F2 CONDUIT BOX LOCATION

- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 180° STEPS.
 2. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR
 3. SEE CHART FOR F2 CAPABILITY. IF YES, BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°

DASH	FRAME	B	C	2F	2FF	BS	F2 CAPABLE	NO. OF MTG. HOLES
1100	254T	11.12	22.49	8.25	-	6.46	NO	4
1150	254T	11.62	22.99	8.25	-	6.96	YES	4
1275	254T	12.87	24.24	8.25	-	8.21	YES	8
1275	256T	12.87	24.24	10.00	-	8.21	NO	4
1325	254T	13.37	24.74	8.25	10.00	8.71	YES	8
1325	256T	13.37	24.74	10.00	-	8.71	YES	4
1475	254T	14.87	26.24	8.25	-	10.21	YES	8
1475	256T	14.87	26.24	10.00	-	10.21	YES	8

		TOLERANCES UNLESS SPECIFIED				DRAWN LMC 8-30-2005	
		DEC.	INCHES			CHK DS 8-30-2005	
		.X	±.1	TITLE OUTLINE		APPD LMC 8-30-2005	
		.XX	±.03	210 FR.-254/56 MTG. ALUMINUM FR.-TEFC		SCALE 1=4	
		.XXX	±.005	MAT'L		REF	
1	REVISED "2FF" COLUMN CN 40215	JJB	06/01/2006	.XXXX	±.0005	FMF	
NO.	REVISION	BY & DATE	CHK	ANG	±7'30"	PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE ss330109ln	SIZE	DRAWING NO. PAGE OF REV.
				DIST	LB	B	SS330109LN 1